MANSFIELD[®]

SUMMIT[®] PRO



THE PROFESSIONAL'S CHOICE

DESIGNED WITH THE SERVICE PLUMBER IN MIND



RELIABLE FLUSH PERFORMANCE



Equipped with a Fluidmaster® fill valve - a name plumber's know and trust - and Mansfield's Rigid Flapper flush valve to provide exceptional and reliable performance every time.

SMARTFASTEN[™] CONNECTION



Our superior SmartFasten[™] tank-to-bowl system **installs quickly** and provides a sturdy connection between tank and bowl that prevents rocking and leaking.

TANK OPTIONS



Available in both **left hand and right hand tanks**, Summit[®] Pro features an attractive and durable color match metal trip lever that will blend nicely with any décor.

Chrome replacement trip levers also available, sold separately.





MANSFIELD[®]



SUMMIT® PRO TOILET AVAILABLE EXCLUSIVELY THROUGH MANSFIELD® WHOLESALE DISTRIBUTORS

FEATURES AND BENEFITS

VERSATILITY

DEPENDABILITY

PERFORMANCE

- 1.6 gpf / 6.0 lpf or 1.28 gpf / 4.8 lpf
- Five bowl configurations in two rough-in sizes: 12" and 10" (see chart)
- Right hand and left hand tanks available
- Color match metal trip lever (Chrome finish available as replacement, sold separately)
- · Available in white
- Fluidmaster[®] fill valve a name plumbers know and trust
- No Call-Back Guarantee (ask your sales rep for details)
- The Mansfield[®] limited lifetime warranty on china, five-year limited warranty on tank trim
- 3' Rigid Flapper flush valve requires less force to flush, is more consistent and uses a simple universal repair part/seal
- Powerful flush performance: 1,000 grams MaP rating at both water consumptions
- SmartFasten[™] tank-to-bowl connection system installs quickly and provides a sturdy, leak-free connection between tank and bowl
- PuraClean[®] easy-to-clean glaze

MODEL NUMBERS	BOWL	TANK	WATER CONSUMPTION (GPF)
	380 RD	376	1.6
		377	1.28
	382 EL	376	1.6
		377	1.28
	384 EL SmartHeight™	376	1.6
		377	1.28
	385 EL SmartHeight™ 10" Rough-In	376	1.6
		377	1.28
	388 RD SmartHeight™	376	1.6
		377	1.28

CERTIFICATIONS



